




INVESTOR IN PEOPLE

The Patent Office
 Concept House
 Cardiff Road
 Newport
 South Wales
 NP10 8QQ




**PRIORITY
 DOCUMENT**
 SUBMITTED OR TRANSMITTED IN
 COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed *A. R. S. J.*

Dated 24 December 2004



THE PATENT OFFICE

A

17 DEC 2003

The
Patent
Office

17DEC03 E860059-1 D02973
P01/7700 0.00-0329196.0 ACCO
UNT. CHA

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference

P650950GB

17 DEC 2003

2. Patent application number

(The Patent Office will fill in this part)

0329196.0

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Business Lines Limited
Harcourt Street
Walkden, Worsley
Manchester
M28 3GN

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

6965198001

4. Title of the invention

A safety device particularly for multiple wheel nuts

5. Name of your agent (if you have one)

Harrison Goddard Foote

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Orlando House
11c Compstall Road
Marple Bridge, Stockport SK6 5HH
United Kingdom

Patents ADP number (if you know it)

00014571002

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Yes

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 6

Claim(s) 2

Abstract 1

Drawing(s) 4 + 4

CF

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 1

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

Herman Goldend Foster

16/12/03

12. Name and daytime telephone number of person to contact in the United Kingdom

Rosemary A Barker

0161 427 7005

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

A safety device particularly for multiple wheel nuts

This invention concerns a safety device for rotatable fasteners, in particular a device for use with a plurality of wheel nuts securing a wheel to a hub.

5

The loosening of wheel nuts on vehicles, such as lorries, is a known safety problem. Safety devices are available in the form of indicators attachable to individual wheel nuts. When a nut loosens an associated indicator, in the form of a ring mounted pointer, rotates and a visual indication is given of loosening. An example of such a

10

device is disclosed in GB2335720 (Business Lines Ltd).

In practice two criteria are used to establish the safety of a wheel nut. Firstly, a given torque is applied to a nut when tightening and, secondly, when secured, a number of threads of a stud on to which a wheel nut is attached should be visible above a secured nut.

15

Current indicators have the disadvantage that it is necessary to apply each indicator individually, which is time consuming on commercial vehicles where five, six, eight or ten or more wheels nuts may be present on each wheel.

20

It is an aim of the present invention to overcome or limit the above disadvantage.

According to the present invention there is provided a safety device for indicating relative rotational displacement of any one of a plurality of rotatably securable fasteners, the device comprising a holder in which a plurality of position indicators for indicating rotational position of the respective fasteners are captively but rotatably mounted and at least one fastener cover which is removably locatable over a fastener and attachable to a corresponding position indicator so as link movement of the fastener and the said position indicator.

25

30

Such a device is particularly suitable for use with wheel nuts where respective indicators serve to indicate if/when respective wheel nuts have become loose.

- 5 A safety device of the invention provides a means for simultaneously applying or removing all position indicators, thus saving time. More importantly, a safety device of the invention provides a means whereby individual fasteners may be adjusted without removing the whole safety device.

- 10 The holder ensures that position indicators may not be individually removed and potentially not replaced. The position indicators may be captively but rotatably mounted in the holder by being a snap fit in to apertures in the holder. Position indicators may be thereby easily replaced if damaged, such as by wear of a wheel nut engaging portion. The holder may be an annular disc or ring.

- 15 The fastener covers ensure that to adjust a fastener the relevant indicator means is disconnected from the fastener but that other indicator means on the holder are not and therefore do not need repositioning. Furthermore by providing fastener covers which are separately removable, the corresponding wheel nut is accessible through the centre of the position indicator and an additional benefit is that thread visibility
20 can be readily checked without removing the whole device from a wheel. Additionally on removal of a fastener cover the linked position indicator is disengaged from the nut so that an operator is not tempted simply to turn the nut back to its original position rather than to a correct torque.

- 25 Position indicators in safety devices of the invention preferably include an indicator portion that is hidden from view by the holder when in a first, 'safe' position, which in use corresponds to an initial fastener position, and is visible outside the holder when in a second position, which in use corresponds to a loosened fastener position.

- 30 An indicator portion of a position indicator, whether or not it is alternatively hidden or visible as just mentioned, may be made highly visible, e.g. by bright colouring,

and holders given a neutral appearance so as to give an at-a-glance indication of a loose fastener.

5 The invention provides a means of seeing a visually striking indication of an unsafe wheel nut condition only when that condition occurs. When the wheel nut is in a safe condition the indicator portion is hidden from sight. Conventional wheel nut indicators do not exhibit this change as such indicators are always visible.

By linking the fastener cover and the indicator device a mechanism is also made available for signalling when a fastener cover has not been replaced. Position
10 indicators used in devices of the invention may be asymmetrical about the longitudinal axis of a wheel nut on a wheel to which they may be attached such that, in use, any position indicator not attached to a fastener cover is flung by centripetal forces on rotation of the wheel into an indicating position. Should a fastener cover
15 not be replaced after tightening a wheel nut then the position indicator will default to the 'loose' or indicating position when a wheel starts to rotate.

The fastener covers may be attachable to the position indicators by means of splines on one or both of the cover and the indicator. Preferably the splines are on the inside
20 of a collar portion of each position indicator to correspond with splines on the outside of each fastener cover. The fastener covers may be attachable to fasteners by means of splines on the inside of the fastener covers.

Safety devices of the invention may comprise a plastics material, in particular
25 polyethylene or polypropylene. Such materials are readily deformable to form a push fit connection between parts.

The invention will be described further, by way of example, with reference to the accompanying drawings, in which;

Figure 1 is a perspective view of a device according to the invention; in which one part of the device is shown in exploded view;

Figure 2 is a perspective view from above of a single position indicator and a fastener cover as illustrated in Figure 1;

Figure 3 is a perspective view of the same parts as Figure 2 but from below;

Figure 4 is a plan view from below of the device shown in Figure 1;

Figure 5 is a top view corresponding to Figure 4; and

Figure 6 is a partial perspective view illustrating the manner of association of a device as shown in Figure 1 with a wheel nut.

A practical embodiment of a safety device (10) according to the invention is made of high density polyethylene and comprises, a holder (12), a plurality of position indicators (30) and an equal number of fastener covers in the form of caps (50).

The holder (12) is in the form of a substantially planar ring, which is provided with a series of identical apertures (14) equally spaced around the ring. The holder has an inner rim with a continuous flange (16), and an outer rim also with a flange (18) but one which is discontinuous so as to leave a gap (20) in the region of each aperture (14). The inner (16) and outer (18) rims are joined across the lower face of the holder, which is adjacent a wheel when in use, by a diagonal wall (22) as shown in figure 4, which serves to give rigidity to the holder (12) and to provide a recess (24).

Each position indicator (30) comprises a body portion or collar (32) and a projecting indicator portion (34) in the form of a triangular pointer. The body or collar (32) has an external annular bearing surface (33) defined between an upper rim (35) and a lower rim (37), a bore (36) provided with splines (38) and a lower region in the form

of an outwardly extending flange (44). The lower rim (37) is coplanar with and extends to form the triangular pointer (34), which is highly coloured, e.g. fluorescent yellow.

5 The body or collar (32) of each position indicator (30) is clipped as a snap fit into a respective aperture (14) in the holder (12), as is apparent in Fig. 1 with the bearing surface (33) held in the aperture by the upper and lower rims (35, 37). With the collar (32) so positioned, the triangular pointer (34) can be accommodated in the respective recess (24) in the holder (12), as shown in Fig. 4. The purpose of the

10 flange (44) is to shroud any washer (42) that may be present on a wheel nut (40) over which it is to be fitted.

The cap (50) comprises a cylindrical wall (56) and a top (54) closing off one end.

15 The wall (56) has a lower portion formed externally with splines (52) for linking with the internal splines (38) of the position indicator (30) in any one of a large number of rotational positions. The wall (56) also has splines (58) on the inside for retention of the cap (50) on a wheel nut (40) by a push fit. The provision of splines (58) enables the cap to be fitted to a hexagonal nut in a plurality of rotational positions such that the pointer (34) can be readily positioned in the recess (24) of the holder. The upper

20 half of the wall (56) and the top (54) of the cap (50) are configured to simulate a nut.

When viewed from below (Figure 4) each pointer (34) is stowed in a respective recess (24) formed by the bottom face of the holder, the inner rim (16), the outer rim (18) and the intervening wall (22) when its respective position indicator (30) is in a

25 normal safe position. However, when an indicator (30) is in a 'loose' position (lower indicator in Figures 4 and 5) its pointer (34) extends out from the recess (24) and clear of the holder (12) such that the pointer (34) will be visible in use if a wheel nut loosens.

30 In use, a device of the invention (10) comprising the holder (12) with a position indicator (30) in every aperture (14) is intended to be placed on a wheel (not shown)

held in place by correctly torqued wheel nuts (40). Each position indicator (30) is oriented with its pointer (34) hidden in a recess (24) in the holder (12) and a cap (50) is placed over each nut (40) to engage with a position indicator (30) such that the caps retain the holder (12) in place on the wheel.

5

After installation, routine inspection of the device is carried out and if a wheel nut (40) has loosened and thus made the relevant pointer (34) visible remedial tightening takes place. This is achieved by removing the relevant cap (50), thus releasing the corresponding position indicator (30). The wheel nut (40) is then tightened to a
10 desired torque, the position indicator (30) re-adjusted to hide its pointer (34) in the recess (22) and the cap (50) is replaced.

15

The skilled person will realise that workshop variants may be practised without departing from the scope of the invention. For example, the position indicator may be rotatably retainable by frictional engagement on the washer of a wheel nut so that
the holder can be retained on a wheel when none of the caps (50) are in place; e.g. when the holder (12) is first being fitted onto the wheel. It will also be appreciated that the invention could be applicable in other situations where a multiplicity of rotatable fasteners are in use and means of indicating their respective rotational
20 positions, indicative of tightness/loosening of same, is required as well as means of remedying same without removal of the entire device.

Claims

1. A safety device for indicating relative rotational displacement of any one of a plurality of rotatably securable fasteners, the device comprising a holder in
5 which a plurality of position indicators for indicating rotational position of the respective fasteners are captively but rotatably mounted and at least one fastener cover which is removably locatable over a fastener and attachable to a corresponding position indicator so as link movement of the fastener and the said position indicator.
- 10 2. A safety device according to claim 1 wherein one or each position indicator includes an indicator portion which, when in a first position, which in use corresponds to an initial fastener position, is hidden from view by the holder, but when in a second position, which in use corresponds to a loosened
15 fastener position is visible outside the holder.
3. A safety device according to claim 1 wherein one or each position indicator includes an indicator portion made highly visible so as to give an at-a-glance indication of a loose nut.
- 20 4. A safety device according to any preceding claim wherein the position indicators are a snap fit in apertures in the holder.
5. A safety device according to any previous claim wherein the holder is an
25 annular disc.
6. A safety device according to any previous claim wherein the or each position indicator is asymmetrical and is thereby capable of moving position in use when not linked to a fastener cover by means of centripetal force about a
30 fastener when in circular motion on a wheel.

7. A safety device according to any previous claim wherein one or each position indicator is attachable to a corresponding fastener cover by means of splines on one or both of the indicator and the cover.

5 8. A safety device according to any previous claim wherein one or each fastener cover is attachable in use to a fastener by means of splines on the fastener cover.

9. A safety device suitable for use with rotatably securable fasteners in the form
10 of wheel nuts on a wheel.

10. A kit of parts for a safety device according to any previous claim comprising a holder, a plurality of position indicators and a plurality of fastener covers.

15 11. A position indicator for use in the safety device of any of claims 1 to 9.

12. A fastener cover for use in the safety device of any of claims 1 to 9.

13. A wheel equipped with a safety device according to any of claims 1 to 9.

20

14. A safety device as hereinbefore described with reference to and as illustrated by any of figures 1 to 6.

25

Abstract

A safety device particularly for multiple wheel nuts

- 5 A safety device (10) comprises a plurality of wheel nut position indicators (30) captively but rotatably mounted in a holder (12). The position indicators are attachable to respective wheel nuts (40) by means of fastener covers (50). When attached, the fastener covers (50) act to secure the device to a wheel and to transfer any rotational movement, i.e. loosening, of a wheel nut (40) to an associated position
- 10 indicator (30). The indicators (30) each have an indicator portion, e.g. a triangular pointer (34) and are so arranged that this portion emerges from the holder and hence becomes visible when any such rotation occurs. By removing a fastener cover (50) an indicator (30) is disengaged from a wheel nut (40) and the individual wheel nut can be tightened without having to remove the entire device (10). The invention helps
- 15 reduce errors in wheel nut maintenance and inspection and allows simultaneous application of a plurality of indicators in one operation.

Figure 6



Figure 1






Figure 2




Figure 3






Figure 5




Figure 4







Figure 6



PCT/GB2004/005250

